

Wall saddle monoblock low temperature MOD. IPAL601C ❄️



Included accessories



LED LIGHT



DOOR MICROSWITCH

Table of cooling capacities in W and cold room m³ - MOD. IPAL601C - R455A

COLD ROOM T.

AMBIENT T.	-15 °C		-20 °C		-25 °C	
	W	m3	W	m3	W	m3
25 °C	1699	16,2	1436	14,8	1193	10,0
32 °C	1548	14,4	1302	12,0	1075	8,7
38 °C	1414	12,5	1184	10,6	971	7,7
43 °C	1295	10,6	1079	8,9	880	6,6

Technical data

Model	IPAL601C
Type	Monoblock (600)
Mounting	Wall
Application	MBP
Expansion	Valve
Defrost	Hot gas
CAT. PED	1
Refrigerant	R455A

Dimensions

Width W	600 mm
Depth D	1004 mm
Height H	800 mm
Net weight	80 kg

Absorption

Power consumption	1200 W
Current consumption	5,8 A

Condenser

Condensation	Air
No. of fan-motors	1
Diameter	300 mm
Air flow	1500 m ³ /h

Evaporator

No. of fan-motors	1
Diameter	300 mm
Air flow	1500 m ³ /h
Air throw	5 m

Compressor

Type	Hermetic
No. of compressors	1 (AJ2464P)
Brand	TECUMSEH
Voltage	220-240/1/50
Displacement	34,5 cm ³

Technical features (standard)

- Structure in zinc-plated metal sheet coated with epoxy primer and powder (RAL 9003);
- Easily removable front cover to facilitate both verification and maintenance operations;
- Internal arrangement of components designed to facilitate their maintenance;
- Hermetic compressors with thermal motor protection;
- Heat exchangers with striped copper and aluminium pipes;
- Air condensation;
- Air evaporation;
- Thermostatic valve expansion;
- Programmable hot gas defrosting;
- Heating cable for condensate drain in both MT and LT;
- Stainless steel tray for condensed water evaporation equipped with a copper coil with cataphoresis coating and an overflow exhaust pipe;
- High-pressure safety pressure switch (automatic reset/fixed setting);
- Electronic control unit;
- Programmable electronic board with touch control display;
- Control unit designed for remote management via Wi-Fi module (optional);
- Cold room light with cable L=2,5m;
- Micro-switch with cable L=2,5m;
- Power cable L=2,5m;
- Packaging with wooden pallet and cardboard (included)

Optional a request

- Plug-in kit th. 100 mm without hooks 600 series;
- Plug-in kit th. 60 mm with hooks 600 series;
- Plug-in kit th. 80 mm with hooks 600 series;
- Plug-in kit th. 100 mm with hooks 600 series;
- Plug-in kit th. 120 mm with hooks 600 series;
- Plug-in kit th. 140 mm with hooks 600 series;
- Low-pressure switch (automatic reset/fixed setting);
- Wi-Fi module for remote management;
- Condenser fan speed control with pressure switch;
- Condenser fan speed control with pressure speed variator;
- Compressor crankcase heater;
- Winter kit;
- Remote control panel with cable of 5/10/15/20m;
- Length increase for machine's power cables, light cable and door micro-switch cable (5/10/15/20m);
- Voltage monitor for three-phase application;
- Cataphoresis treatment on evaporator and/or condenser;
- Packaging with wooden cage;