

**SPLIT SYSTEM WITH LOW-NOISE  
CONDENSING UNIT TECHNICAL DATA  
SHEET TECUMSEH TFH2480**

**TECHNICAL DATA**

Code	ISSL042AET
Type	Low-noise (1100)
Noise	38 dBA 10m
Application	Low Temp.
Expansion	Valve
Refrigerant	R452A
CAT. PED	1

**CONDENSING UNIT DIMENSIONS**

Width W	1155
Depth D	450
Height H	750
Net weight	123 kg

**PIPE FITTINGS**

Liquid line	Ø 10
Suction	Ø 16

**ABSORPTION**

Power consumption (W)	1538 (W)
Current consumption (A)	4,3 (A)
Power defrost (W)	1950 (W)

**CONDENSER**

Condensation	Aria
Fans no.	1
Diameter	Ø 400
RPM	900 g/m

**EVAPORATOR**

Fans no.	2
Diameter	Ø 300
Air flow	2875 m3/h
Air throw	11 m

**COMPRESSOR**

Type	HERMETIC
Compressors no.	1 TFH2480
Brand	TECUMSEH
Voltage	400/50Hz
Displacement	54,3 (cc)



Indicative product image



LED lamp




Door micro-switch

**REFRIGERATION CAPACITY TABLE (W - M<sup>3</sup>) OF SPLIT SYSTEM  
WITH LOW-NOISE CONDENSING UNIT TFH2480 Refrigerant R452A**

COLD ROOM T.	-15 °C		-20 °C		-25 °C	
AMBIENT T.	W	M <sup>3</sup>	W	M <sup>3</sup>	W	M <sup>3</sup>
25 °C	2665	34,5	2225	28,0	1816	18,9
32 °C	2407	30,4	1992	23,9	1605	16,0
38 °C	2127	25,4	1724	19,4	1348	12,7
43 °C	1927	20,5	1546	14,9	1189	9,4

**EVAPORATOR DIMENSIONS**



## STANDARD TECHNICAL FEATURES

- Self-supporting casing in zinc-plated metal sheet coated with epoxy powder (RAL7047);
- Sound insulation on the compressor side;
- Hermetic compressor with internal protection of the motor;
- Compressor muffler (if required);
- High-performance air condenser with aluminium fins and grooved cooper tubes;
- Axial external rotor fan-motor (900 rpm) 220V\_50Hz;
- Condenser fan speed regulator;
- Liquid receiver with safety valve;
- Drier filter to be welded;
- Humidity indicator to be welded;
- Solenoid valve on the liquid line to be welded;
- HP+LP pressure switch with automatic reset;
- Rapid shut-off valves up to d.18mm; shut-off valves to be welded from d.22mm on;
- Built-in power and control electrical box;
- Aluminium and copper ventilated evaporator with electric defrost;
- Expansion by thermostatic valve;
- Condensed water tray (tube heater for low temperature models);
- Condenser - evaporator connecting cables, length 2,5 meters;
- Wired remote control panel with large display, cable length 2,5 meters;
- Wired door micro-switch, cable length 2,5 meters;
- Cold room light with wired LED lamp, cable length 2,5 meters;
- Power cable length 2,5 meters;
- Condensing unit under nitrogen pressure;
- PED directive compliant units;
- Packaging included (pallet+cardboard);

## OPTIONAL ON REQUEST

- Wi-Fi module for remote management;
- Compressor crankcase heater;
- Oil separator;
- Liquid separator;
- Refrigerant charge;
- Cables kit for evaporator, cold room light, door micro-switch and remote panel (from 5 to 30 meters);
- Cable kit for remote control panel (from 5 to 30 meters);
- Pipe connections SAE flare kit up to Ø18 in suction (from 2,5 to 30 meters);
- Pre-charged pipe connections kit up to Ø18 in suction (from 2,5 to 30 meters);
- Pipe connections kit to be welded up to Ø18 in suction (from 2,5 to 30 meters);
- Water condensation or mixed air/water condensation;
- Cataphoresis treatment on evaporator and/or on condenser;
- Electrical fan;
- Packaging with wooden cage;